

UNITED STATES DEPARTMENT OF COMMERCE United States Patent and Trademark Office Address: COMMISSIONER FOR PATENTS P.O. Box 1450 Alexandria, Virginia 22313-1450 www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/820,770	04/09/2004	Ichiro Koiwa	OKI.651	8824
20987 7590 11/29/2007 VOLENTINE & WHITT PLLC			EXAMINER	
ONE FREEDO	M SQUARE		HOANG, QUOC DINH	
11951 FREEDO RESTON, VA	OM DRIVE SUITE 1260 20190)	ART UNIT	PAPER NUMBER
1001011, 111	. 20170		2818	
			MAIL DATE	DELIVERY MODE
			11/29/2007	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

		4 /			
	Application No.	Applicant(s)			
	10/820,770	KOIWA, ICHIRO			
· Office Action Summary	Examiner	Art Unit			
	Quoc D. Hoang	2818			
The MAILING DATE of this communication ap Period for Reply	pears on the cover sheet with the o	correspondence address			
A SHORTENED STATUTORY PERIOD FOR REPL WHICHEVER IS LONGER, FROM THE MAILING C - Extensions of time may be available under the provisions of 37 CFR 1. after SIX (6) MONTHS from the mailing date of this communication If NO period for reply is specified above, the maximum statutory period Failure to reply within the set or extended period for reply will, by statut Any reply received by the Office later than three months after the mailing earned patent term adjustment. See 37 CFR 1.704(b).	OATE OF THIS COMMUNICATION 136(a). In no event, however, may a reply be tir will apply and will expire SIX (6) MONTHS from e. cause the application to become ABANDONE	N. nely filed the mailing date of this communication. (D) (35 U.S.C. § 133).			
Status					
1)⊠ Responsive to communication(s) filed on <u>12 (</u>	October 2007.				
	s action is non-final.				
• • • • • • • • • • • • • • • • • • • •	Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under <i>Ex parte Quayle</i> , 1935 C.D. 11, 453 O.G. 213.				
Disposition of Claims					
4) ⊠ Claim(s) <u>2-8,15 and 18-27</u> is/are pending in the day of the above claim(s) <u>4-6,19-22 and 24-26</u> 5) ☐ Claim(s) is/are allowed. 6) ⊠ Claim(s) <u>2,3,7,8,15,18,23 and 27</u> is/are reject 7) ☐ Claim(s) is/are objected to. 8) ☐ Claim(s) are subject to restriction and/	<u>6</u> is/are withdrawn from considerated.	tion.			
Application Papers					
9)☐ The specification is objected to by the Examin					
10) The drawing(s) filed on is/are: a) □ accepted or b) □ objected to by the Examiner.					
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a). Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).					
11) The oath or declaration is objected to by the E					
Priority under 35 U.S.C. § 119					
12) Acknowledgment is made of a claim for foreig a) All b) Some * c) None of: 1. Certified copies of the priority documer 2. Certified copies of the priority documer 3. Copies of the certified copies of the pri application from the International Burea * See the attached detailed Office action for a list	nts have been received. nts have been received in Applicat ority documents have been receiv au (PCT Rule 17.2(a)).	ion No ed in this National Stage			
Attachment(s) 1) Notice of References Cited (PTO-892) 2) Notice of Draftsperson's Patent Drawing Review (PTO-948)	4) Interview Summan Paper No(s)/Mail D	Pate			
3) Information Disclosure Statement(s) (PTO/SB/08) Paper No(s)/Mail Date	5) Notice of Informal 6) Other:	Patent Application			

10/820,770 Art Unit: 2818

DETAILED ACTION

Continued Examination Under 37 CFR 1.114

1. A request for continued examination under 37 CFR 1.114, including the fee set forth in 37 CFR 1.17(e), was filed in this application after final rejection. Since this application is eligible for continued examination under 37 CFR 1.114, and the fee set forth in 37 CFR 1.17(e) has been timely paid, the finality of the previous Office action has been withdrawn pursuant to 37 CFR 1.114. Applicant's submission filed on 10/12/207 has been entered.

Response to Amendment

2. Amendment filed on 10/12//2007 has been entered. Claims 1, 9-14, 16, 17 have been canceled. Claims 2-8, 15, and 18-27 are pending in the application.

Claim Rejections - 35 USC § 103

- 3. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:
 - (a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negatived by the manner in which the invention was made.
- 4. Claims 2, 3, 7, 8, 15, 18, 23 and 27 are rejected under 35 U.S.C. 103(a) as being unpatentable over Aoki et al., (US Pat No. 6,033,953) (hereinafter "Aoki") in view of Lu., (US Pat No. 5,679,596).

Regarding claim 2, Aoki teaches a ferroelectric capacitor comprising: a bottom electrode (38) (col. 1, lines 14-57 and Fig. 14);

10/820,770 Art Unit: 2818

a plurality of projection electrodes (convex parts 38a) formed on the bottom electrode (col. 1, lines 14-57 and Fig. 14);

a ferroelectric layer (40) formed on the bottom electrode and the projection electrodes (col. 1, lines 14-57 and Fig. 14); and

a top electrode (37) formed on the ferroelectric layer, wherein a thickness of the ferroelectric layer on the projection electrodes is less than a thickness of the ferroelectric layer on the bottom electrode (col. 1, lines 14-57 and Fig. 14).

Aoki teaches a plurality of projection electrodes, but fails to teach wherein spacing between central portions of each projection electrode has a range from 10 % to 20% of a size of the ferroelectric capacitor.

However, Lu teaches wherein spacing between central portions of each projection electrode (14b) has a range from 1.5 % to 75% of a size of the ferroelectric capacitor (col. 4, line 50 through col. 5, line 65 and Fig. 5). It is noted that the size of the ferroelectric capacitor is considered the width (2,000-10,000 Å) of the bottom electrode 11 (col. 4, lines 40-43), the width of the projection electrode 14b is between about 50-500 Å (col. 5, lines 17-18), and the spaces 14a between the projection electrode 14b are between about 100-1000 Å (col. 5, lines 19-21). Hence, after calculating, the spacing between central portions of each projection electrode 14b has a range from 1.5 % to 75% of a size of the ferroelectric capacitor. Since Aoki and Lu are all from the same field of endeavor, the purpose disclosed by Lu would have been recognized in the pertinent art of Aoki. It would have been obvious to a person of ordinary skill in the art at the time of the invention was made to provide spacing between central portions of each

10/820,770 Art Unit: 2818

projection electrode in order to increase the surface area of the bottom electrode, therefore to obtain the desired increased capacitance as taught by Lu, column 5, lines 24 through col. 6, line 3. Although Lu's percentage range (1.5 % to 75%) is not the claimed range (10 % to 20%), this does not define patenable over Aoki in view of Lu since it has been held where the general conditions of a claim are disclosed in the priort art, discovering the optimum or workable range involves only routine skill in the art. In re Aller, 105 USPQ 233.

Regarding claim 3, Aoki teaches a ferroelectric capacitor comprising:

- a bottom electrode (38) (col. 1, lines 14-57 and Fig. 14);
- a plurality of projection electrodes (convex parts 38a) formed on the bottom electrode (col. 1, lines 14-57 and Fig. 14);
- a ferroelectric layer (40) formed on the bottom electrode and the projection electrodes (col. 1, lines 14-57 and Fig. 14); and

a top electrode (37) formed on the ferroelectric layer, wherein a thickness of the ferroelectric layer on the projection electrodes is less than a thickness of the ferroelectric layer on the bottom electrode (col. 1, lines 14-57 and Fig. 14).

Aoki teaches a plurality of projection electrodes, but fails to teach wherein wherein a size of each projection electrode has a range from 5 % to 10% of a size of the ferroelectric capacitor.

However, Lu teaches wherein a size of each projection electrode (14b) has a range from 0.5 % to 25% of a size of the ferroelectric capacitor (col. 4, line 50 through col. 5, line 65 and Fig. 5). It is noted that the size of the ferroelectric capacitor is

10/820,770 Art Unit: 2818

considered the width (2,000-10,000 Å) of the bottom electrode 11 (col. 4, lines 40-43), the size of each projection electrode is considered the width of the projection electrode 14b, which is between about 50-500 Å (col. 5, lines 17-18). Hence, after calculating, a size of each projection electrode has a range from 0.5 % to 25% of a size of the ferroelectric capacitor. Since Aoki and Lu are all from the same field of endeavor, the purpose disclosed by Lu would have been recognized in the pertinent art of Aoki. It would have been obvious to a person of ordinary skill in the art at the time of the invention was made to provide a size of each projection electrode has a range from 5 % to 10% of a size of the ferroelectric capacitor in order to increase the surface area of the bottom electrode, therefore to obtain the desired increased capacitance as taught by Lu, column 5, lines 24 through col. 6, line 3. Although Lu's percentage range (0.5 % to 25%) is not the claimed range (5 % to 10%), this does not define patenable over Aoki in view of Lu since it has been held where the general conditions of a claim are disclosed in the priort art, discovering the optimum or workable range involves only routine skill in the art. In re Aller, 105 USPQ 233.

Regarding claim 7, Aoki teaches a ferroelectric capacitor comprising:

- a bottom electrode (38) (col. 1, lines 14-57 and Fig. 14);
- a plurality of projection electrodes (convex parts 38a) formed on the bottom electrode (col. 1, lines 14-57 and Fig. 14);
- a ferroelectric layer (40) formed on the bottom electrode and the projection electrodes (col. 1, lines 14-57 and Fig. 14); and

10/820,770 Art Unit: 2818

a top electrode (37) formed on the ferroelectric layer, wherein a thickness of the ferroelectric layer on the projection electrodes is less than a thickness of the ferroelectric layer on the bottom electrode (col. 1, lines 14-57 and Fig. 14).

Aoki teaches a plurality of projection electrodes, but fails to teach wherein the projection electrodes are arranged evenly spaced on the bottom electrode.

However, Lu teaches wherein the projection electrodes (14b) are arranged evenly spaced on the bottom electrode 11 (col. 4, line 50 through col. 5, line 65 and Fig. 5). It is noted that the evenly spaced between the projection electrodes 14b is the width of the crevice or space 14a (col. 5, lines 19-21). Since Aoki and Lu are all from the same field of endeavor, the purpose disclosed by Lu would have been recognized in the pertinent art of Aoki. It would have been obvious to a person of ordinary skill in the art at the time of the invention was made to provide evenly spaced between the projection electrodes in order to increase the surface area of the bottom electrode, therefore to obtain the desired increased capacitance as taught by Lu, column 5, lines 24 through col. 6, line 3. Also, the limitations "so that cores of polarization inversion within the ferroelectric layer extend from the projection electrodes" is considered an intended use of the claimed invention. A recitation of the intended use of the claimed invention must result in a structural difference between the claimed invention and the prior art in order to patentably distinguish the claimed invention from the prior art. If the prior art structure is capable of performing the intended use, then it meets the claim.

10/820,770 Art Unit: 2818

Regarding claim 8, Aoki teaches wherein the bottom electrode 38 and the projection electrodes 38a are made of a same material (platinum) (col. 1, lines 50-55 and Fig. 14).

Regarding claim 15, Aoki teaches a ferroelectric capacitor comprising:

- a first electrode (38) (col. 1, lines 14-57 and Fig. 14);
- a second electrode (37) (col. 1, lines 14-57 and Fig. 14);
- a plurality of third electrodes (convex parts 38a) on the first electrode;

a ferroelectric layer (40) which is sandwiched between the first electrode and the second electrode, and on the third electrodes, wherein a thickness of the ferroelectric layer on the third electrodes is less than a thickness of the ferroelectric layer on the second electrode (col. 1, lines 14-57 and Fig. 14);

Aoki teaches a plurality of third electrodes, but fails to teach wherein the third electrodes are arranged evenly spaced.

However, Lu teaches wherein the third electrodes (14b) are arranged evenly spaced (col. 4, line 50 through col. 5, line 65 and Fig. 5). It is noted that the evenly spaced between the projection electrodes 14b is the width of the crevice or space 14a (col. 5, lines 19-21). Since Aoki and Lu are all from the same field of endeavor, the purpose disclosed by Lu would have been recognized in the pertinent art of Aoki. It would have been obvious to a person of ordinary skill in the art at the time of the invention was made to provide evenly spaced between the third electrodes in order to increase the surface area of the first electrode, therefore to obtain the desired increased capacitance as taught by Lu, column 5, lines 24 through col. 6, line 3. Also, the

10/820,770 Art Unit: 2818

limitations "so that cores of polarization inversion within the ferroelectric layer extend from the third electrodes" is considered an intended use of the claimed invention. A recitation of the intended use of the claimed invention must result in a structural difference between the claimed invention and the prior art in order to patentably distinguish the claimed invention from the prior art. If the prior art structure is capable of performing the intended use, then it meets the claim.

Regarding claim 18, Aoki teaches wherein the first electrode (38) and the third electrodes (38a) are made of a same material (platinum) (col. 1, lines 50-55 and Fig. 14).

Regarding claim 23, Aoki teaches wherein the bottom electrode 38 and the projection electrodes 38a are made of a same material (platinum) (col. 1, lines 50-55 and Fig. 14).

Regarding claim 27, Aoki teaches wherein the bottom electrode 38 and the projection electrodes 38a are made of a same material (platinum) (col. 1, lines 50-55 and Fig. 14).

Conclusion

5. Any inquiry concerning this communication or earlier communications from the examiner should be directed to Quoc Hoang whose telephone number is (571) 272-1780. The examiner can normally be reached on Monday-Friday from 8.00 AM to 5.00 PM.

If attempt to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Steven Loke can be reached on (571) 272-1657. The fax phone numbers of

10/820,770 Art Unit: 2818

the organization where this application or proceeding is assigned are (571) 273-8300 for regular communications and (571) 273-8300 for After Final communications.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see http://pair-direct.uspto.gov. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free).

Quoc Hoang Patent examiner/AU 2818

> QUOC D. HOANG PRIMARY PATENT EXAMINER

Unahorn/ 11/25/2017